

## SECTION 09222

### BITUMINOUS CONCRETE PATCHING

**Description:**

The work under this item shall consist of the permanent patching of any pavement surfaces or pedestrian passways which have become rutted, broken, damaged or otherwise unserviceable, and at such other locations as the Engineer may designate.

**Materials:**

The materials furnished and used in this work shall conform to the requirements of Form 816 Section 4.06 and M.04. The specific material to be used for patching shall be as directed by the Engineer and shall be Class 1, 2, or 4.

**Construction Methods:**

Patching shall be done only at the locations and at such time as is deemed necessary by the Engineer. Prior to placing the patching material, the areas to be patched shall be cleaned of dirt and other debris and shall be dry. Areas shall be squared off with a neat finished edge. Gravel base and subbase shall be compacted by methods approved by the Engineer. Where compaction cannot be achieved, contractor is to remove and replace gravel base and/or subbase to suitable depth with processed aggregate. Compaction of the patching material shall be attained by methods approved by the Engineer. Contractor to adhere to specifications provided in the Contract Documents.

**Method of Measurement:**

The quantity of bituminous patching material to be included for payment will be determined by the square yards installed. Compaction of the gravel base and/or subbase is incidental to this item. The quantity of processed aggregate material to be included for payment will be paid for at the contract unit price per ton. The excavated gravel base and/or subbase material below the bottom of the installed bituminous concrete patch will be paid for at the contract unit price per cubic yard for Roadway Excavation..

**Basis of Payment:**

This work will be paid for at the contract unit price per square yard for "Bituminous Concrete for Patching," complete in place, which price shall include furnishing all materials, equipment, tools, labor and work incidental thereto. Where indicated in the Contract, separate contract unit prices may be established for work within an overlay project and external to other operations.